

Fastmark M9+

Easy Implementation and Easy to Use
for All-Around Thermal Printing



PAL®: The AMT Datasouth Difference

Implementation is made easy with our plug and play capability - saving the IT team time and effort. In addition to popular emulations, our proprietary PAL® programming language resides in the smart printer allowing us to load an app that will accept your data stream and convert, format and print to fit your organization's requirements, including both linear and 2D barcodes. You can unplug any existing printer and replace it with the Fastmark® M9+. And, ongoing service and support, including future changes to the PAL® app, if needed, are available for the life of the printer.

- Easy to use touchscreen interface
- Print speeds up to 8 ips
- Highest quality barcodes
- 203 and 300 dpi models available
- Our powerful and versatile "PAL"
- Zebra and other popular emulations

The M9+ is ready for loading custom PAL[®] applications



PRINTER SPECIFICATIONS INCLUDE:

Printer Model	Fastmark M9+
Resolution	203, 300 dpi
Command Set	PAL Plus, Eltron, Zebra, Datamax
Printing Method	Direct Thermal/Thermal Transfer
Print Speed	Up to 8 ips – 203 dpi Up to 6 ips – 300 dpi
Max Print Width	4.25 inches – 203 dpi 4.16 inches – 300 dpi
Media Width	0.8" - 4.7"
Max Length	1000 inches – 203 dpi 450 inches – 300 dpi
Media Outside Diameter	8.0"
Media Thickness	2.36 - 11.0 mil
Dimension	(W) 9.8" x (D) 17.2" x (H) 10.8"

Weight	19.8 lbs
Display	Touch Color LCD
Sensors	Gap transmissive, black bar reflective
Memory	64MB SDRAM 128 MB Flash
Processor	32-bit
Interfaces	RS-232, USB, USB HOST, Ethernet Optional: GPIO, Bluetooth, WiFi 802.11 b/g/n (slot adapter)
Barcodes	Linear and 2D
Ribbon Core	1"
Ribbon Outside Diameter	3.2" Ink coated inside/outside
Cutter	User Option
Real Time Clock	Standard
Limited Warranty	Printer: 2 years Print Head: 1 year
Agency	UL, UL c, CE, TUV, FCC, Energy Star



Identification Systems Group
www.IdentificationSystemsGroup.com
info@IdentificationSystemsGroup.com

